

## 8000 Series Diaphragm Electric Pump

The 8000 Series diaphragm pump is SHURflo's most widely used pump with spherically shaped valves and automatic demand switch, these pumps are the pump of choice for applications requiring consistent, dependable operation and priming. Up to 1.8 GPM (6.8 l/min).

### Features:

- Pressures up to 150 PSI (10.3 bar)
- Self priming up to 8 vertical feet (2.4 m)
- NSF, UL and CSA listed
- Can run dry without damage
- Built in check valve
- EPDM valves, Santoprene® diaphragm



The models listed below are the most popular:

Model	Description
94-437-00	Low Voltage Beverage Pump System 8000 (corded) pump w/115-24 VAC Transformer, 60 psi demand switch /0.95 GPM open flow 3/8" barb fittings Mounting board Product Data Sheet)
8005-733-155	Delivery PUMP (non-corded) 115VAC, 60 psi demand switch/1.4 GPM open flow, 45 psi bypass 1/2" MPT-Male ports Product Data Sheet
8005-791-255	Delivery PUMP (non-corded) 230VAC, 50 psi demand switch /1.1 GPM open flow, 45 psi bypass 3/8" NPT-Female ports Product Data Sheet
8025-213-236	Water Boost PUMP (corded) 115VAC, 60 psi demand switch /1.4 GPM open flow 3/8" NPT-Female ports
8025-933-289	Water Boost PUMP (corded) 115VAC, 90 psi demand switch /1.4 GPM open flow 3/8" NPT-Female ports
8095-213-296	Water Boost PUMP (non-corded) 230VAC, 90 psi/1.4 GPM open flow

	3/8" NPT-Female ports, Product Data Sheet
8005-932-260	Carbonator PUMP (non-corded) 115VAC, 100 psi/1.4 GPM open flow, 120 psi bypass 3/8" NPT-Female ports Product Data Sheet
8095-902-260	Carbonator PUMP (non-corded) 230VAC, 100 psi/1.4 GPM open flow, 100 psi bypass 3/8" NPT-Female ports, VDE approved Product Data Sheet (n/a)
8008-997-300	High Flow Double Headed Carbonator PUMP (corded) 115VAC, 150 psi/3.8 GPM open flow, Quick-disconnect ports Product Data Sheet