

PRIMARY REGULATORS 5700 SERIES



Taprite regulators have the highest flow rate in the industry. Robust design delivers performance, reliability and is unlikely to experience freeze up problems. Extremely durable and user friendly polycarbonate bonnets make adjustments a snap! Pull cap to adjust the pressure and push back to lock it in.

The TAPRITE ADVANTAGE

- High CO2 volumetric flow provides continuity in product dispensing
- Primary regulators connect directly to gas source
- Recommended operating pressure be limited to 2/3 of the gauge range for maximum accuracy
- UL approved per UL252 class IV rating for CO2
- Polycarbonate bonnet will not chip, break or fade
- 10 Micron filter built in to keep contaminants out of regulator
- One repair kit for primary and secondary
- Used primarily for Soda and Beer but can be used for other applications.



T5741PMHPBK



3248 Northwestern Dr., San Antonio, Texas 78238 • 210-523-0800 • Fax 210-646-6009 • sales@taprite.com

taprite.com



MODEL NUMBERS



Model Number	Description
T5740HP160BK	Body only, black cap, no fittings
T5741PMHP	1PX1P, 160lb & 2000lb gauges, ¼ FL (w/check) red cap
T5741PMHPB	1PX1P. 160lb & 2000lb gauges, ¼ FL (w/check) blue cap
T5741PMHPBK	1PX1P, 160lb & 2000lb gauges, ¼ FL (w/check) black cap
T5741PMHPBKGP	1PX1P, 160lb & 2000lb gauges, ¼ FL (w/check) black cap, gauge guard
T5741PMHPGPS	1PX1P 160lb & 2000lb gauge, ¼ FL (w/check) red cap, gauge boot
T5745HPBK	1PX5P, 160lb & 2000lb, gauges 5X ¼ FL (w/check) red cap
T5752HP-02	2PX2P, 160lb & 2000lb gauges, ¼ FL (w/check) red cap

Wall Mount Regulators

Model Number	Description
T5741WMHP	1PX1P, 160lb & 2000lb gauges, ¼ FL in/out, red cap
T5741WMHP-3	1PX1P , 160lb & 2000lb gauges, ¼ FL (w/check) red cap w/3ft hose
T5741WMHP-6	1PX1P, 160lb & 2000lb gauges, ¼ FL (w/check) red cap w/6ft hose

T5741PMHPBK

