



Features

- High-capacity activated carbon filtration makes ice free of taste or odor, and protects equipment against corrosive chlorine.
- Patented IsoNet scale inhibiting technology helps protect equipment against scale (lime-scale) and corrosion.
- Gradient-density sediment filtration reduces dirt and other suspended particulates as small as 1/2 micron.
- Improves ice maker operating efficiency.
- Reduces maintenance and extends equipment life.
- 1/4 turn Quick-Twist cartridge makes changing filters quick and easy.
- IFQ1 & IFQ2 are NSF Certified under Standard 42.


IFQ SERIES FILTER SYSTEM

| Model Number | Description | Max.Cube ICE Maker Capacity lbs (kg) Per Day | Flow Rate Max. gpm (lpm) | Pressure Max. psi | Max. Operating Temp. °F° (°C) | Micron Rating | Approx. Shipping Weight lbs (kg) |
|--------------|---------------|--|-----------------------------|----------------------|-------------------------------------|------------------|--|
| IFQ1 | Single Filter | 1000 (454.4) | 1.5 (5.7) | 125 | 100 (38) | .5 | 4 (1.8) |
| IFQ2 | Dual Filter | 2400 (1090.6) | 3.0 (11.4) | | | | 8 (3.6) |

SINGLE INLINE FILTER CARTRIDGES

| Model Number | Description | Max.Cube ICE Maker Capacity lbs (kg) Per Day | Flow Rate Max. gpm (lpm) | Pressure Max. psi | Max. Operating Temp. °F° (°C) | Micron Rating | Approx. Shipping Weight lbs (kg) |
|--------------|---|--|-----------------------------|----------------------|-------------------------------------|------------------|--|
| IF14C | Single Inline Cartridge 1/4" compression | 600 (272) | 1.0 | 100 | 100 (38) | 10 | 2 (.9) |
| IF18C | Single Inline Cartridge 3/8" compression | | | | | | |

**IFQ Series
Filter Systems**




IFQ1
15"H x 6"W x 4"D
(381 mm x 152 mm x 102 mm)




IFQ2
16"H x 10"W x 6"D
(406 mm x 254 mm x 102 mm)

**Single Inline
Filter**



IFI4C, IFI8C
11" x 2.5"
(279 mm x 57 mm)

**Replacement
Filter Cartridges**



IOMQ
12.75" x 4"
(324 mm x 102 mm)

All filter systems include:

Filter cartridge with FDA approved scale inhibitor, inlet shut-off valve, gauge and quick-connect fittings.

*IOMQ replacement cartridges for use with IFQ1 & IFQ2 manifold filter systems.

FILTER SIZING CHART

| Ice-O-Matic Cube Ice Maker | Ice-O-Matic Flake Ice Maker | Ice-O-Matic Pearl Ice® Maker | Recommended Ice-O-Matic Water Filter |
|--|-----------------------------|------------------------------|--|
| ICEU070, 150, 220, 226, 300, ICEO250, O320, O400, O406, O500, O520, O606 | MFIO500, EF250, EF450 | GEMO450 | IFQ1 (Single Manifold cartridge Filter System) IFI4C or IFI8C (Single inline Filter System) |
| ICEO806 | MFIO800 | GEMO650, O956 | IFQ1 (Single Manifold cartridge Filter System) |
| ICEI006, 1406, 1506, ICE 1806, 2106 | MFIO800, MFI2406 | GEM1256 | IFQ2 (Dual Manifold cartridge Filter System) |

Extended Warranty Program

- Buy a new Ice-O-Matic Water Filter System (IFQ1 or IFQ2) with a new ICE Series™ Cube ice maker, replace the filter cartridge every 6 months, and Ice-O-Matic will extend the limited cuber evaporator warranty to 7 years parts and labor (U.S. and Canada only).
- New ice maker and filter must be installed at the same time.
- Ice maker and water filter registration cards must be sent to Ice-O-Matic within 10 days of installation. Water filter warranty card must include the filter serial number(s).
- An additional registration card must be sent in for each new filter installed (filters have individual serial numbers). This must be done every 180 days (6 months) or less.
- Program is available with all Ice-O-Matic IFQ1 or IFQ2 water filter systems.
- Replacement filter must be Ice-O-Matic models.