# *Bev-Seal* Ultra® Cabled Barrier Tubing/Hose Bundle



## Bev-Seal Ultra® Series 974H Cabled Barrier Tubing/Hose Bundle

Construction: Flushable Bev-Seal Ultra® Series 235 syrup tubes, each color coded, individually numbered and branded with date codes for traceability. In each configuration, there are two 3/8" ID PET-lined Bevlex® Plus Series 180 hoses specifically included to carry water at pressures up to 300 psig at 70°F. In addition one 1/4" ID polyethylene Bevlex® 170 hose has been included to carry carbon dioxide gas at pressures up to 240 psig at 70°F. The cable construction and silver-gray "low-friction" extruded jacket allows for convenient one-step installation. All component lines as well as the bundle itself carry NSF-51 and NSF-61 listings and are branded accordingly. Sequential footage marks on the bundle jacket add to the ease of installation.

Part Number	Standard Package	Description & Configuration for Each Bundle Film Wrapped — Silver-Gray Extruded Jacket	Max. Bundle OD		ight Pkg kgs.	Min. Bend Radius (in)	Clamp Size (mm)
974H-00100012-01 974H-00100012-02 974H-00100012-05	100' Coil 200' Reel 500' Reel	10 – .380 x .500 <b>Bev-Seal Ultra</b> <sup>®</sup> 235 Syrup Tubes 2 – .375 x .593 <b>Bevlex</b> <sup>®</sup> <b>Plus</b> 180 Water Hoses 1 – .265 x .457 <b>Bevlex</b> <sup>®</sup> 170 Gas Hose	2.3"	83 189 466	38 86 212	10"	14.0 15.7 13.3
974H-00120012-01 974H-00120012-02 974H-00120012-05	100' Coil 200' Reel 500' Reel	12 – .380 x .500 <b>Bev-Seal Ultra</b> <sup>®</sup> 235 Syrup Tubes 2 – .375 x .593 <b>Bevlex</b> <sup>®</sup> <b>Plus</b> 180 Water Hoses 1 – .265 x .457 <b>Bevlex</b> <sup>®</sup> 170 Gas Hose	2.5"	92 197 510	42 90 231	12"	14.0 15.7 13.3
974H-00140012-01 974H-00140012-02 974H-00140012-05	100' Coil 200' Reel 500' Reel	14 – .380 x .500 <b>Bev-Seal Ultra</b> <sup>®</sup> 235 Syrup Tubes 2 – .375 x .593 <b>Bevlex</b> <sup>®</sup> <b>Plus</b> 180 Water Hoses 1 – .265 x .457 <b>Bevlex</b> <sup>®</sup> 170 Gas Hose	2.6"	100 226 554	45 103 252	. •	14.0 15.7 13.3
974H-00160012-01 974H-00160012-02 974H-00160012-05	100' Coil 200' Reel 500' Reel	16 – .380 x .500 <b>Bev-Seal Ultra</b> <sup>®</sup> 235 Syrup Tubes 2 – .375 x .593 <b>Bevlex</b> <sup>®</sup> <b>Plus</b> 180 Water Hoses 1 – .265 x .457 <b>Bevlex</b> <sup>®</sup> 170 Gas Hose	2.8"	108 248 598	49 113 272		14.0 15.7 13.3

**Bevlex®** is a registered trademark of Accuflex Industrial Hose Ltd., Guelph, ON, Canada **Bev-Seal Ultra®** is a registered trademark of Kuriyama of America, Inc., Schaumburg, IL, USA

Because we continually examine ways to improve our products, we reserve the right to alter specifications without notice.



## **Cautionary Statement**

All Products sold and distributed by Accuflex Industrial Hose, Ltd. are in the nature of commodities and they are sold by published specifications and not for particular purposes, uses or applications. Purchaser shall first determine their suitability for the intended purposes, uses or applications and shall either conduct its own engineering studies or tests, or retain qualified engineers, consultants or testing laboratories and consult with them before determining the proper use, suitability or propriety of the merchandise or Products for the intended purposes, uses or applications.

Accuflex Industrial Hose, Ltd. ("Seller") does not recommend the Products for any particular purpose, use or application, and the Purchaser or user thereof shall assume full responsibility for the suitability, propriety, use and application of the Products. Purchaser shall follow all instructions contained in Seller's catalogs, brochures, technical bulletins and other documents regarding the Products. The Products, including but not limited to, hose, tubing or couplings, may fail due to the use or conveyance of substances at elevated or lowered temperatures or at excessive pressure, the conveyance of abrasive, injurious, flammable, explosive or damaging substances.

Hose or tubing used in bent configurations will be subjected to increased abrasion. Hose clamps or couplings may loosen after initial installation and all sections of hose and tubing including connections, couplings, clamps, conductivity and bonding should be inspected frequently, regularly and consistently, and should be replaced, adjusted or re-tightened for the avoidance of leakage, for the prevention of injuries or damages, and for general safety purposes. Except as indicated in its Limited Warranty, Seller shall not be liable or responsible for direct or indirect injuries or damages caused by or attributed to the failure or malfunction of any Products sold or distributed by it.

Purchasers or users of the Products should frequently and consistently undertake inspections and protective measures with respect to the use and application of Products, which should include the examination of tube and cover, conditions of the hose or tubing, and the identification, repair or replacement of sections showing cracking, blistering, separations, internal and external abrasions, leaking or slipped couplings or connections and make proper proof tests.

## **Limited Warranty**

The Products sold or distributed by Seller are warranted to its customers to be free from defects in material and workmanship at the time of shipment by us, subject to the following provisions.

ALL WARRANTY CLAIMS SHALL BE MADE WITHIN SIX (6) MONTHS AFTER SELLER SHIPPED THE PRODUCTS. SELLER'S LIABILITY HEREUNDER IS LIMITED AT SELLER'S EXCLUSIVE DISCRETION, TO 1) THE PURCHASE PRICE OF ANY PRODUCTS PROVING DEFECTIVE; 2) REPAIR OF ANY DEFECTIVE PRODUCT OR PART THEREOF; OR 3) REPLACEMENT OF ANY DEFECTIVE PRODUCT OR PART UPON ITS AUTHORIZED RETURN TO SELLER.

THIS WARRANTY IS IN LIEU OF AND EXCLUDES ALL OTHER WARRANTIES. EXPRESSED, IMPLIED, STATUTORY, OR OTHERWISE CREATED UNDER APPLICABLE LAW INCLUDING, BUT NOT LIMITED TO, THE WARRANTY OF

MERCHANTABILITY AND THE WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL SELLER OR THE MANUFACTURER OF THE PRODUCT BE LIABLE FOR SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING LOSS OF PROFITS, WHETHER OR NOT CAUSED BY OR RESULTING FROM THE NEGLIGENCE OF SELLER AND/OR THE MANU-FACTURER OF THE PRODUCT, UNLESS SPECIFICALLY PROVIDED HEREIN. IN ADDITION, THIS WARRANTY SHALL NOT APPLY TO ANY PRODUCTS OR PORTIONS THEREOF WHICH HAVE BEEN SUBJECTED TO ABUSE, MISUSE, IMPROPER INSTALLATION, MAINTENANCE, OR OPERATION, ELECTRICAL FAILURE OR ABNORMAL CONDITIONS, AND TO PRODUCTS WHICH HAVE BEEN TAMPERED WITH, ALTERED, MODIFIED, REPAIRED, REWORKED BY ANYONE NOT APPROVED BY SELLER, OR USED IN ANY MANNER INCON-SISTENT WITH THE PROVISIONS OF THE "CAUTIONARY STATEMENT" ABOVE OR ANY INSTRUCTIONS OR SPECIFICATIONS PROVIDED WITH OR FOR THE PRODUCT.

10/2004



#### **Accuflex Industrial Hose, Ltd.**

Subsidiary of Kuriyama of America, Inc.

8000-A Ronda Dr. Canton, MI 48187-2067 Phone: (734) 451-0080 Toll-free FAX: (800) 877-0544

International FAX: (734) 451-0544

Web Site: http://www.accuflex.com

E-Mail: sales@accuflex.com

### **Kuri Tec Corporation**

Box 21052, L P M P O 140 Roy Boulevard Brantford, ON, Canada N3R 7W9 Phone: (519) 753-6717

FAX: (519) 753-7737

Web Site: http://www.kuritec.com

E-Mail: sales@kuritec.com

Bevlex® is a registered trademark of Accuflex Industrial Hose Ltd., Guelph, ON, Canada Bev-Seal Ultra® is a registered trademark of Kuriyama of America, Inc., Schaumburg, IL, USA