

# Accuflex Beverage Transfer Products

## Flexible Insulated Drain Hoses

### Featuring Tigerflex™ Brand Drain Hose

#### Features and Benefits:

- **Convuluted Construction** - Provides exceptional kink resistance that provides a very tight bend radius for difficult installations.
- **Smooth Bore** - Minimizes internal flow restrictions.
- **Antimicrobial Insulation** - Inhibits growth of bacteria and other micro-organisms.
- **Snug Fitting Insulation** - Minimizes air entrapment beneath the insulation and condensation that might otherwise form.
- **Convenient Sizes** - Available ID sizes are 1/2", 3/4" and 1" to fit most applications.
- **Convenient Lengths** - hoses are furnished in nominal 72" lengths.
- **Phthalate Free**



#### General Applications:

- Drains on ice makers and beverage dispensing units

#### Construction:

Smooth bore flexible PVC with rigid PVC helix reinforcement.

#### Service Temperature:

-4°F (-20°C) to 150°F (+65°C)



**For under-the-counter and fountain head areas; keeps condensation from forming on the Drain Hose and then dripping on floor area.**

### Nominal Specifications

Part Number	Nominal				Working Pressure (psi)		Vacuum Rating Hg (in) at 68°F		Min. Bending Radius at 68°F (in)	Weight (lbs/ft)
	ID (in)	ID (mm)	OD (in)	OD (mm)	68°F	104°F	68°F	104°F		
A15-DHG050	1/2	12.7	0.67	17.0	38	20	23	13	0.50	0.12
A15-DHG20MM	3/4	20.2	1.06	26.8	36	18	22	12	0.75	0.16
A15-DHG27MM	1	26.5	1.36	34.5	36	18	22	12	1.00	0.25

## Flexible Non-Insulated Drain Hoses

### Featuring Tigerflex™ Brand Drain Hose

#### Features and Benefits:

- **Convuluted Construction** - Provides exceptional kink resistance that provides a very tight bend radius for difficult installations.
- **Smooth Bore** - Minimizes internal flow restrictions.
- **Convenient Sizes** - Available ID sizes are 1/2", 3/4" and 1" to fit most applications.
- **Convenient Lengths** - Hoses are furnished in 100 ft. and 25 ft. lengths.
- **Phthalate Free**



#### General Applications:

- Drains on ice makers and beverage dispensing units

#### Construction:

Smooth bore flexible PVC with rigid PVC helix reinforcement.

#### Service Temperature:

-4°F (-20°C) to 150°F (+65°C)



### Nominal Specifications

Part Number	Nominal				Working Pressure (psi)		Vacuum Rating Hg (in) at 68°F		Min. Bending Radius at 68°F (in)	Weight (lbs/ft)
	ID (in)	ID (mm)	OD (in)	OD (mm)	68°F	104°F	68°F	104°F		
DHG050X100	1/2	12.7	0.67	17	38	20	23	13	0.50	0.07
DHG050X25	1/2	12.7	0.67	17	38	20	23	13	0.50	0.07
DHG20MMX100	3/4	20.2	1.06	26.8	36	18	22	12	0.75	0.13
DHG20MMX25	3/4	20.2	1.06	26.8	36	18	22	12	1.00	0.20
DHG27MMX100	1	26.5	1.36	34.5	36	18	22	12	1.00	0.20
DHG27MMX25	1	26.5	1.36	34.5	36	18	22	12	1.00	0.20

Because we continually examine ways to improve our products, we reserve the right to alter specifications without notice.