

SECONDARY REGULATORS 5200 SERIES



Taprite regulators have the highest flow rate in the industry. Robust design delivers performance, reliability and is unlikely to experience freeze up problems. Extremely durable and user friendly polycarbonate bonnets make adjustments a snap! Pull cap to adjust the pressure and push back to lock it in.

The TAPRITE ADVANTAGE

- High CO2 volumetric flow provides continuity in product dispensing
- Primary regulators connect directly to gas source
- Recommended operating pressure should be limited to 2/3 of the gauge range for maximum accuracy
- UL approved per UL252 class IV rating for CO2
- Polycarbonate bonnet will not chip, break or fade
- 10 Micron filter built in to keep contaminants out of regulator
- One repair kit for primary and secondary
- Used primarily for Soda but can be used for other applications.



T5261SN



3248 Northwestern Dr., San Antonio, Texas 78238 • 210-523-0800 • Fax 210-646-6009 • sales@taprite.com
taprite.com



MODEL NUMBERS



Model Number	Description
T5260SN100	Body assembly for 100lb gauge gold cap
T5260SN100BK	Body assembly for 100lb gauge black cap
T5260SN160	Body assembly, 0-120 PSI, 160lb gauge gold cap
T5260SN160BK	Body assembly, 0-120 PSI, 160lb gauge black cap
T5260SN60	Body assembly for 60lb gauge gold cap
T5260SN60BK	Body assembly for 60lb gauge black cap
T5261SN	1P X 1P 100lb gauge, 1/4" flare inlet, 1/4" flare check valve outlet, gold cap
T5261SN60	1P X 1P 60lb gauge, 1/4" flare inlet, 1/4" flare check valve outlet, gold cap
T5261SNBK	1P X 1P 100lb gauge, 1/4" flare inlet, 1/4" flare with check valve out black cap
T5261SNBL	1P x 1P 100lb gauge, 1/4" flare inlet/thru, 1/4" flare with check valve outlet blue cap
T5261SND	1P X 1P, 30lb gauge, 1/4" flare inlet, 1/4" flare with check valve outlet gold cap
T5261ST	1P X 1P, 100lb gauge, 1/4" flare inlet, 1/4" flare with shutoffs outlet gold cap
T5272SN	2P X 2P, 100lb gauge, 1/4" flare inlet/out, 1/4" flare with check valve outlet, metal brackets, gold cap
T5272SNG	2P X 2P, 100lb gauge, 1/4" flare inlet/thru, 1/4" flare with check valve outlet, glide brackets, gold cap
T5272SN-375	2P X 2P, 160lb gauge, 3/8" flare outlet, 1/4" flare check valve outlet gold cap
T5276SND	2P X 2P, 100lb & 30lb gauges, 1/4" barb inlet/outlet + vertical manifold (4 barbs+ 1 flare), metal brackets, gold cap



T5261SN

